



# MSIS

TRUSTED SPECIALIST

## HOT WASH

Our innovative hot wash unit is certified for use in hazardous areas and is uniquely designed to include a wheeled, stainless steel lifting frame tested in accordance with DNV 2.7-1 allowing for maximum manoeuvrability within confined areas. The unit delivers an instant and constant supply of hot water of up to 55°C at a pressure up to 2250 psi and an impressive flow rate of 13 L/min – efficiently working on the harshest cleaning operations with or without chemicals, reducing man hours and minimising downtime.

- CE marked and suitable for use in ATEX Category II Zone 1 areas
- NORSOK compliant
- Portable, wheeled and lightweight frame
- Internal storage for lance and hoses
- Robust, full stainless steel construction
- Electricity supply - standard 63 amp socket



### OVERVIEW

This unit has been manufactured to the highest standard for use in harsh environments with an emphasis on compliance, quality, ease of use and maintenance.

With an established reputation for quality, reliability and service, we do not let our clients down. Our ESR team is available 24/7 to ensure the provision of a rapid response service, ensuring that we consistently meet our clients' operational objectives.

### CONTACT US

Our extensive range of equipment is available for rental or purchase. Please contact our specialist technical support team at [ESRInfo@msisgroup.com](mailto:ESRInfo@msisgroup.com) to discuss your specific requirements.

### COMPLETE WITH:

- 50 ft of 1" anti-static water supply hose and fittings
- 50 ft of 3/8" HP twin-wired jetting hose and fittings
- Lance gun assembly
- Chemical feed connection and suction hose
- Copy of operating manual
- Certification package
- Additional hoses and accessories available on request

### SPECIFICATION:

- Dimensions (L x W x H): 120 x 75 x 118 cm
- Weight: 500 kg
- Standard 63 Amp Socket
- Mains supply isolator & emergency stop
- Dual Voltages: 415 V/50 Hz – 57 Amp  
480 V/60 Hz – 61 Amp
- 4 x 9 kW heaters
- 4 kW motor for pump (50/60 Hz)
- Maximum discharge pressure 150 Bar
- Maximum discharge rate 13.6 L/min
- DNV certified Lifting frame and lifting sling

PRODUCT INFORMATION



**FOR MORE INFORMATION  
CALL US ON +44 (0) 1467 673 900**

Admiralty Base, Shore Road,  
Invergordon IV18 0RE

T +44 (0) 1349 854 454 E [info@msisgroup.com](mailto:info@msisgroup.com)

Kirkwood Commercial Park,  
Thainstone, Inverurie AB51 5NR

T +44 (0) 1467 673 900 E [ESRInfo@msisgroup.com](mailto:ESRInfo@msisgroup.com)

W [www.msisgroup.com](http://www.msisgroup.com)  
T @MSISGroup  
in MSIS Group